


Rockchip® ARM Cortex A55 RK3568, 1 x RJ45



Features

- Rockchip® ARM Cortex-A55 (quad-core, up to 2.0 GHz)
- On board 3200/4GB LPDDR4X SDRAM
- On board 32G Flash ROM Max 64GB
- Support WIFI and Blue Tooth
- Support 1 x GbE LAN
- 2 x UART, 2 x RS232, 2 x USB3.0(OTG), 4 x USB2.0
- 1 x eDP, 1 x 24-bits Dual CH LVDS, 1 x HDMI®
- Support 4K H.264/265 video decoding and 1080P H.264/265 format video encoding


Packing List

PART NUMBER	DESCRIPTION	QTY
—	OTH-ARK3-356843A1 M/B	1

Specifications

SYSTEM	
MB FORM FACTOR	ARM
CPU	Rockchip® ARM Cortex-A55 quad-core (up to 2.0 GHz) with 1 TOPS NPU
CHIPSET	Rock Chip® RK809-5 PMU
MEMORY	Onboard LPDDR4X 3200MT/s 4GB standard (8GB optional)
WAKE ON LAN	Yes
WATCHDOG TIMER	255 Levels
SECURITY	Intel® PTT (Integrated fTPM)
DIMENSION (W X D)	120.0 (W) x 72.0 (D) mm (4.7" x 2.8")
POWER	
POWER REQUIREMENT	DC-in 12V
POWER ON MODE	AT / ATX
CONNECTOR	DC Jack
DISPLAY	
GPU	Mali-G52 MP2 GPU
LVDS	1 x LVDS (Max. Resolution: 1920 x 1200 @60Hz)
eDP	1 x eDP (Max Resolution: 2560 x 1600@60Hz)
HDMI®	1 x HDMI® (Max Resolution: 4096 x 2304@60Hz)
MULTIPLE DISPLAY	Support 3 Displays
AUDIO	
CODEC	2-channel HD Audio
COMBO	1 x Combo Audio Jack for Line-Out / Mic-In
AMPLIFIER	3W
LAN	
ETHERNET	1 x Realtek RTL8211F-CG GbE 1 x AW-CM358 (802.11 b/g/n 2.4GHz Wi-Fi + Bluetooth 4.2)
USB PORT	
USB	4 x USB 2.0 2 x USB 3.0 (co-layout OTG)
SERIAL PORT	
COM	Internal Header for 2 x RS-232
INTERNAL I/O	
GPIO	4-Bit
SMBUS	Yes
ADDITIONAL	1 x Debug 2 x UART (UART8/UART9, UART8 Co-Lay RS-485) 1 x Inverter
STORAGE	
MINI PCI-E	1 x Full Size Mini-PCIe
eMMC	Onboard 32GB eMMC, Optional Up to 64GB
EXPANSION	
SIM	1 x SIM Card Slot
OTHERs	
OTHER	1 x Micro SD
ENVIRONMENT & CERTIFICATION	
OPERATING TEMPERATURE	-10°C - 60°C (14°F - 140°F)
STORAGE TEMPERATURE	-20°C - 70°C (-4°F - 158°F)
CERTIFICATION	CE/FCC Class A LVD
ESG DECLARATION	EU RoHS, REACH (Option), China RoHS

Dimension Unit: mm



Ordering Information

PART NUMBER	OTH-ARK3-356843A1
CPU	Rockchip® ARM Cortex-A55 (Quad-core, up to 2.0 GHz)
MEMORY	Onboard LPDDR4x 3200MT/s up to 4GB
SECURITY	Intel® PTT (fTPM)
POWER REQUIREMENT	DC-in 12V
GPU	Mali-G52 MP2 GPU
LVDS	1 x LVDS
eDP	1 x eDP
HDMI	1 x HDMI®
MULTIPLE DISPLAY	Support 3 Displays
ETHERNET	1 x GbE
ETHERNET	1 x WiFi/BT
USB	4 x USB 2.0
USB	2 x USB 3.0
COM	2 x RS-232
MINI PCI-E	1 x Full mini PCIe
eMMC	eMMC 32GB
SIM	1 x SIM Card Slot
OTHER	1 x Micro SD
OPERATING TEMPERATURE	-10°C ~ 60°C (14°F ~ 140°F)