

HBJC900C59B-3160B

1. INTEL® Braswell-D J3160 SOC Chipset
2. Onboard INTEL® Braswell-D J3160 2.24GHz QC CPU
3. On board 4G DDR3L 1600 Memory
4. Support DirectX 12 3D Graphics Acceleration
5. Integrated HD Audio CODEC
6. Support 2*PCI Express Gigabit LAN
7. Support 1*DP Port and 2*HDMI Ports
8. Support 3*USB3.0 Ports
9. Support 1*M-SATA Socket (Full size)
10. Support 2*Mini PCIe Socket (1*Full size +1* Half size)
11. Support Vibration protection function
12. Support Thunder Protection Function
13. 25mm thin, slice design



Specifications

| | | |
|-----------------------------|---------------------|------------------------------------|
| Case | Panel Material | Aluminum |
| | Color | Option |
| | Coating Requirement | Spray Paint + Anode |
| | Cooling Mode | Fan less Fully sealed design |
| System Specification | Form Factor | uTX |
| | Processor | INTEL® Braswell-D J3160 2.24GHz/QC |
| | GPU | INTEL® HD Graphics 400 |
| | System Chipset | INTEL® Braswell-D J3160 (SOC) |
| | System Memory | 4G/DDR3L |
| | BIOS | 64MB SPI Flash ROM |
| | Ethernet | 2*Realtek® RTL8111G Gigabit LAN |
| | Audio | Realtek® ALC662 HD Audio |
| | Storage | 1* M-SATA connector |
| | WIFI Module | Option |
| | Optical Device | N/A |
| | Expansion | 2*PCI-E mini card for WLAN |
| Display Output | 1*DP+2*HDMI | |

| | | |
|------------------|-----------------------|---|
| | Display | Three Independent Displays |
| | Resolution | 3840x2160@ 30Hz、2560x1600@60Hz |
| | I.O Port | 3*USB3.0、1*Line-out、1*MIC、2*RJ45、1*Power Button、1*DC-Jack |
| | Power Adapter | DC-IN (9~24V) |
| | OS Support | Windows 7/8.1/10 |
| | Temperature | Operating: -10 ~ +60°C |
| | Humidity | 20%~90% (non condensing) |
| | Dimension | 148.0mm*116.0mm*25.0mm |
| | Certification | FCC CE (Option) |
| Accessory | Antenna | J05-ANT-AN2400-F |
| | ADAPTER 12V/3.33A 40W | HLMAP-FSP040-F |
| | Power Cord | Change according to shipping area |
| | WALL Mount | HCS900MWM01B-F |